

## SPECIALTY TRAILER TIRE



**STZC**  **HEAT-LESS**

- The special HEAT-LESS (using heat resistant compounding) technologies helps to slow down the tire aging and extend the tire life
- Double steel belts for enhanced strength helping puncture resistance and vehicle towing stability
- Long-life and low rolling resistance compound to offer long original treadwear and to promote fuel economy
- Full nylon cap available in all sizes for improved durability

| Size        | LR/PR  | Service Index | Tread Depth |       | Standard Rim | Section Width |      | Overall Diameter |       | Max. Load |           | Max. Air |     | TT/TL    |
|-------------|--------|---------------|-------------|-------|--------------|---------------|------|------------------|-------|-----------|-----------|----------|-----|----------|
|             |        |               | mm          | 32nds |              | mm            | inch | mm               | inch  | kg        | lbs       | kpa      | psi |          |
| ST175/80R13 | C/6PR  | 91/87L        | 7.5         | 9     | 5.0J         | 177           | 6.97 | 610              | 24.02 | 615/545   | 1360/1200 | 350      | 50  | Tubeless |
| ST185/80R13 | D/8PR  | 99/95L        | 7.5         | 9     | 5.0J         | 184           | 7.24 | 626              | 24.65 | 775/690   | 1710/1520 | 450      | 65  | Tubeless |
| ST205/75R14 | C/6PR  | 100/96L       | 7.8         | 10    | 5.5J         | 203           | 7.99 | 664              | 26.14 | 800/710   | 1760/1570 | 350      | 50  | Tubeless |
| ST215/75R14 | C/6PR  | 102/98L       | 7.5         | 9     | 6.0J         | 216           | 8.50 | 678              | 26.69 | 850/750   | 1870/1650 | 350      | 50  | Tubeless |
| ST215/75R14 | D/8PR  | 108/103L      | 7.8         | 10    | 6.0J         | 216           | 8.50 | 678              | 26.69 | 1000/875  | 2200/1930 | 450      | 65  | Tubeless |
| ST205/75R15 | C/6PR  | 101/97L       | 7.8         | 10    | 5.5J         | 203           | 7.99 | 689              | 27.13 | 825/730   | 1820/1610 | 350      | 50  | Tubeless |
| ST205/75R15 | D/8PR  | 107/102L      | 7.8         | 10    | 5.5J         | 203           | 7.99 | 689              | 27.13 | 975/850   | 2150/1870 | 450      | 65  | Tubeless |
| ST225/75R15 | C/6PR  | 107/102L      | 8.2         | 10    | 6.0J         | 223           | 8.78 | 719              | 28.31 | 975/850   | 2150/1870 | 350      | 50  | Tubeless |
| ST225/75R15 | D/8PR  | 113/108L      | 8.2         | 10    | 6.0J         | 223           | 8.78 | 719              | 28.31 | 1150/1000 | 2540/2200 | 450      | 65  | Tubeless |
| ST225/75R15 | E/10PR | 117/112L      | 8.2         | 10    | 6.0J         | 223           | 8.78 | 719              | 28.31 | 1285/1120 | 2830/2470 | 550      | 80  | Tubeless |
| ST235/80R16 | E/10PR | 124/120L      | 8.2         | 10    | 6.5J         | 235           | 9.25 | 782              | 30.79 | 1600/1400 | 3520/3080 | 550      | 80  | Tubeless |
| ST235/85R16 | F/12PR | 128/124L      | 8.2         | 10    | 6.5J         | 235           | 9.25 | 806              | 31.73 | 1800/1600 | 3960/3520 | 660      | 95  | Tubeless |
| ST225/90R16 | D/8PR  | 121/117L      | 8.2         | 10    | 6.0J         | 220           | 8.66 | 808              | 31.81 | 1450/1285 | 3200/2830 | 450      | 65  | Tubeless |