

TERRA KING II



- Tractor tires with high flotation technology
- Optimal structure provides higher load capacity at low air pressure with relative lower soil compaction due to the wider contact area
- Especially suitable for sensitive soil and plants
- Unique anti-worn surface compound and anti-aging sidewall compound, which ensure longer lifespan
- Bestseller of Terra series in most popular size in the market
- Combine with all the features from TFP series except more compact HF-2 pattern
- Improved compound for even better performance and lifespan, wise choice for the cost-performance ratio



Longer
Tire Life



Field
Protection



High
Flotation



Reduced Soil
Compaction



High Loads
At Low Pressure



TERRA KING II

TRA: HF-2

Tire Size	Load/ Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity Kg					
								Speed Km/h					
			mm						mm	mm	KPa	Static	10
1000/50R25	175A8/175B	TL	50.0	36.00	1640	1060	280	15870	10350	7660	7380	6900	6900

TERRA KING II

TRA: HF-2

Tire Size	P. R.	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity Kg					
								Speed Km/h					
			mm					mm	mm	KPa	Static	10	15
66×43.00-25	10	TL	50.0	36.0TH	1702	1054	170	11925	7110	5940	5040	4500	4500
	12						210	13250	7900	6600	5600	5000	5000
	20						340	17755	10585	8840	7500	6700	6700
	26						450	21200	12640	10560	8960	8000	8000