



IS standard



AGRIMAX PRO HARVEST



PRODUCT DATA SHEET



Radial



D



200

Technologies



VF Technology



Steel Belted



Reinforced Bead



Reinforced Shoulder



Strong Casing



High Speed

Performance



Cut and Chip Resistance



Self-Cleaning



Traction



Durability



High Load Capacity



AGRIMAX PROHARVEST

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation. The tire casing, engineered to guarantee high load capacity, combined with the CFO (Cyclic Field Operation) technology allows AGRIMAX PROHARVEST to handle temporary overloads during operations like harvesting, reducing stress and wear on the tire. Once the load is reduced, the tire returns to its standard operating condition, thus extending its service life and improving operational efficiency. The open shoulder design improves traction on rough and wet terrain while facilitating the ejection of mud and debris, ensuring smooth transitions from field to road and enhancing safety. On the field and on the road AGRIMAX PROHARVEST can reach up to 65km/h making your transit operation easier and faster thus improving overall productivity.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version	
			Rec.	Alt.							
	Ø 26"	VF 620/70 R 26 CFO NEWSIZE	173 D	DW 21 B	DW 20 B ; DW 23 B	620	1528	670	4590	725	SB
	Ø 32"	VF 800/70 R 32 CFO	187 D	DW 28 B	DW 27 B ; DW 30 B	804	1933	846	5817	925	SB
		VF 900/60 R 32 CFO	193 D	DW 30 B	-	881	1900	837	5712	900	SB
		VF 1000/55 R 32 CFO	197 D	36.00 VA (multi-piece)	-	1006	1900	841	5703	900	SB
	Ø 38"	VF 1020/55 R 38 CFO NEWSIZE	200 D	36.00 VA (multi-piece)	-	1010	2060	-	57	975	SB

SB: Steel Belted



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partial or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkirsha Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.